

CAROUSEL SCREEN PRINTING MACHINE

S-TYPE XTREME

UNLEASH THE POWER OF PRECISION



The S-Type Xtreme redefines performance with unmatched speed, reliability, and efficiency. Engineered for those who demand the best, it outperforms every competitor in its class. With advanced, time-saving features built in, the S-Type Xtreme takes productivity to the next level—so you can do more, in less time, with total confidence.



UP TO 1,400 INDEXES PER HOUR



UP TO 18 PALLETS



UP TO 16 COLOURS

www.uniscreen.co.nz





Power, Precision, and Performance—Redefined.

The S-Type Xtreme isn't just another press—it's a productivity powerhouse. Packed with smart, time-saving features, it's built to slash setup times and keep your operation running at full speed. Need even more flexibility? Our Long Stroke (LS) models can be customized to fit your unique workflow and budget.

At the heart of it all is the M-Touch Pro—our sleek, tablet-style control unit that puts total command at your fingertips. Intuitive, responsive, and designed for real-world use, it makes operation effortless. And with full WiFi connectivity, you get real-time tech support from anywhere in the world—so your press stays running, and your business keeps moving forward.

ADJUSTABLE SCREEN HOLDERS FOR EVERY FRAME SIZE.

Seamlessly adapt to any job with screen holders designed to fit a wide range of frame sizes—fast, secure, and built for maximum flexibility.

TOTAL COMMAND AT EVERY STROKE.

Dial in perfection with independent flood and print speed controls—engineered for precision, powered for performance.

ADJUST IN SECONDS. DOMINATE FOR HOURS.

With tool-free front and rear stroke length adjustment, you get instant precision and zero downtime—because speed and control shouldn't come with compromises.

PERFECT PRESSURE. EVERY STATION. EVERY TIME.

With a dedicated squeegee pressure regulator on every station, you get consistent, dialed-in prints across the board—no guesswork, just flawless control.

STAY IN CONTROL. WITHOUT LEAVING THE CONSOLE.

Make flash cure adjustments instantly from the main control unit—streamlining your workflow with precision, power, and zero interruptions.

PRECISION STARTS HERE.

Full micro-registration with a true zero starting position—engineered for pinpoint accuracy and lightning-fast setups, right from the first print.

Specifications (per model)

	SPSX-08	SPSX-10	SPSX-12	SPSX-14	SPSX-16	SPSX-18
Number of pallets	8	10	12	14	16	18
Max. number of print stations	6	8	10	12	14	16
Max. diameter 43 x 50 cm / 16.9 x 19.7 "	385 cm / 152 "	420 cm / 165 "	450 cm / 177 "	490 cm / 193 "	528 cm / 208 "	570 cm / 224 "
Max. diameter 45 x 55 cm / 17.7 x 25.6 "	415 cm / 163 "	455 cm / 179 "	500 cm / 197 "	542 cm / 213 "	584 cm / 230 "	625 cm / 246 "
Max. diameter 45 x 70 cm / 17.7 x 27.6 "	n/A	n/A	n/A	n/A	614 cm / 241 "	n/A
Max. diameter 50 x 70 cm / 19.7 x 31.5 "	460 cm / 181 "	505 cm / 199 "	550 cm / 217 "	595 cm / 234 "	n/A	n/A
Machine weight (kg / lbs)	1,450 / 3,200	1,680 / 3,700	1,900 / 4,190	2,100 / 4,630	2,650 / 5,840	2,870 / 6,330
Average air consumption (l/min)	220 (7.8 cfm)	280 (9.9 cfm)	340 (12.0 cfm)	400 (14.1 cfm)	460 (16.2 cfm)	520 (18.4 cfm)
Rec. air supply (l/min)	350 (12.4 cfm)	400 (14.1 cfm)	450 (15.9 cfm)	500 (17.7 cfm)	600 (21.2 cfm)	650 (23 cfm)