# **MUTOH**



## **Key Specifications**

Print Technology Drop-on-demand micro piezo inkjet 2 AccuFine HD print heads - staggered setup Print Head Head Heights Low: 1.5 mm / Middle: 2.0 mm / High: 2.5 mm Nozzle Configuration 400 nozzles x 8 lines (each head) Ink Setup C, M, Y, K Resolutions Up to 1200 x 2400 dpi Drop Mass Range (pl) 3.4 to 10.6 pl MUTOH genuine VerteLith RIP included

# **Media Specifications**

media opecinications	
Maximum Media Width	1625 mm – 64"
Maximum Print Width	1615 mm – 63.58"
Maximum Media	ž 1.3 mm
₱₦i��®\$ance Accuracy	±0.25 mm or ±0.1% of the print
	distance (whichever is greater)
	Environmental Conditions: Temperatur
	22°C-30°C - Humidity: 40%-60% RH
Media measurements	Standard non motorized roll o¤ system
	Ø 200 mm / 2" and 3" / 30 kg
Motorized Take Up	30 kg – start/stop linked to
Systems	printing – roll up Ø 150 mm



#### **Performance**

Print Mode	Productivity (m∏/h)
Draft	17.2
High Speed	15.3
Production	11.5
Quality	9.4
High Quality	5.8

## **Ink Specifications**

Ink Type	AQUAFUZE™ waterbased UV inks*
Ink Colours/Volume	C, M, Y, K: Pack - 1000 ml
Key Characteristics	• Low odour
	Does not contain CMR substances
	GHS hazard-free
	Scratch-resistant with a soft feel
	T h i n , durable ink film
	<ul> <li>L o w temperature drying for diverse substrates</li> </ul>
Certification	GREENGUARD Gold certified – category Wallpaper, AgBB 2024, French
	VOC- and CMR-regulation: Class A+, Belgian VOC regulation

<sup>\*</sup>AQUAFUZE is a registered trademark of Fujifilm Group

# **Power Consumption / Environmental Conditions / Dimensions**

During Printing	1.400 W or less	
Sleep Mode	41 W or less	
Power Supply	Voltage: AC 100V $\sim$ 120V $\pm$ 10 % / AC 200V $\sim$ 240V $\pm$ 10 % Frequency: 50/6	0Hz
Environmental conditions – printer operation	Temperature: 20°C~32°C Humidity: 40%~60% RH – no condensing	
Environmental conditions – accuracy	Temperature: $22^{\circ}\text{C}\sim30^{\circ}\text{C}$ Humidity: $40\%\sim60\%$ RH – no condensing	
<b>EXEMPO</b> Mensions	(W) 2770 $\times$ (D) 895 $\times$ (H) 1611 mm (with ink pack adapters mounted)	
Weight	186 kg (Printer body: 146 kg, stand: 32 kg, winder: 8 kg)	

# **Auckland Head Office**





5 Basalt Place, East Tamaki, Auckland, New Zealand



+64 9 274 3831



rene@uniscreen.co.nz

