

### Specifications

Specific	ayons		
Xpertuet		XPJ-461UF	XPJ-661UF
Printing system		On-demand prezo drive system	
Set medla	Size (W×D)	483mm (19") ×329mm (12.95")	483mm (19") ×594mm (23.4")
	Height	up to 70mm (2.75") [with standard table] / up to 150mm (5.9") [without standard table]	0 ~ 150mm (5.9*)
		up to 70mm (2.75") [with optional vacuum table]	
	Weight	up to 5kg (11lbs) [with standard table] / up to 8kg (17.6lbs) [without standard table]	6kg (13,2lbs)
		up to 4kg (8.8lbs) [with optional vacuum table]	UKB (10,2IUS)
Max printable size (W×D)		483mm (19") ×329mm (12.95")	483mm (19") ×594mm (23.4")
Table height adjustment		PG handle (handle 1.5mm / round)	Automatic
lnk	Туре	UV LED Ink (UH21 Ink / US11 Ink)	
	Ink set	4 colours (K, C, M, Y) / 6 colours (K,C,M,Y, white, varnish)	
	Capacity	220ml Ink cartridge (K,C,M,Y, white, varnish)	
	No. of slot	6	
Print resolution		1440/1080/720dpl (Total 3 modes)	
Interface		Ethernet (10BASE-T / 100BASE-TX)	
Power requirements		AC100-120V±10%, 50/60Hz±1Hz	
Operation noise		Standby: 51dB or less / Printing with standard table: 63dB or less /	Standby: 49dB or less / Printing with vacuum table: 69dB or less
		Printing with optional vacuum table: 70dB or less	
Printable environment		Temperature: 20 32°C Humidity: 40 60%RH (non condensing)	
Electrical power consumption		Sleep mode: 20W or less / Ready to print: 40W or less / Operation: 195W or less	Sleep mode: 20W or less /Ready to print: 40W or less / Operation: 300W or less
Dimensions (W×D×H) /Weight		1,188mm (46.8") ×972mm (38.2") ×597mm (23.5") [Front cover closed] / weight: 95kg (209lbs)	1,188mm (46.8") ×1,627mm (64.1") ×604mm (23.8") [Front cover closed] / weight: 130kg (287lbs)
		1,188mm (46.8") ×972mm (38.2") ×1,011mm (39.8") [Front cover opened]	1,188mm (46.8") ×1,627mm (64.1") ×1,196mm (47.01") [Front cover opened]
		1,188mm (46.8") ×1,025mm (40.4") ×597mm (23.5") [PG handle cover opened]	
Printer Driver		Bundled	
RIP software		VerteLith	
Rotary Jig		N/A	Optional
Stand		N/A	Included

- \* The vacuum table is optional for XPJ-461UF
- The vacuum audic is optional to Ara-Button in Specifical tools are subject to change without notice.

  The printer driver is included in the XPJ-461UF / 661UF.

  Ink adhesion will vary among media type and brand, Individual testing is required in function of your specific application.

  As white ink settles at the bottom of cartridge, please be sure to shake lightly once a day before use.



### **Auckland Head Office**



5 Basalt Place, East Tamaki, Auckland, New Zealand



+64 9 274 3831



rene@uniscreen.co.nz





# Xpertuet 461UF 661UF



# Everything you want in a simple and compact desktop UV LED printer










Print tactile 2.5D graphics such as embossed text, braille, and textured decorations. XPJ-661UF is ideal for premium 2.5D printing grater than 1mm thick (XPJ-461UF eeds manual adjustment)

### **LED** touch panel



Beautifully designed, intuitive, high visibility electrostatic touch panel for easy to use operation. Supports 8 languages

### Vacuum table holding media firm



Vacuum table can hold thin media firmly. Control 5 steps of vacuum power directly from the operation panel. (Optional for the XPJ-461UF)

### **Obstacle detection system**








MUTOH **EMPLOYEE OF THE YEAR** 





## Local Dimming Control (Patent pending)

